

	1 2 3	5 6
	PIN PLATING CODES:	
\bigcirc	XXXXX-1YY 30u"/0.76u MIN (SEE NOTE 14) OVER 50u"/1.27u MIN Ni	(3.) PIN MATERIAL: PHOS BRONZE.
	XXXXX-2YY	MEASURED WITH PART IN RESTRAINED CONDITION.
	XXXXX—3YY	5. TWO SIDES OF PIN TIPS NOT PLATED. TYPICAL BOTH ENDS.
	XXXXX—4YY XXXXX—4YYHLF 100u"/2.54u MIN Sn OVER 50u"/1.27u MIN Ni (SEE NOTE 15)	(6) 2LBS/0.9KG MIN PIN RETENTION IN EITHER DIRECTION.
	XXXXX-5YY	7. MILITARY BERGSTIK HEADER P/N XXXXX—XYY—MIL
	XXXXX-6YY 30u"/0.76u MIN (SEE NOTE 14) OVER 50u"/1.27u MIN Ni	NOT AVAILABLE.
	XXXXX-7YY 30u"/0.76u MIN Au OVER 50u"/1.27u MIN Ni	(8) ±.010/0.25 TOL APPLIES TO ALL "G" TAILS EXCEPT
	XXXXX-8YY 15u"/0.38u MIN Au OVER 50u"/1.27u MIN Ni	INDICÁTED PARTS ON TABLE WHERE +.010/0.25000/0.00 APPLIES.
<u> </u>	XXXXX—9YY	(9.) NOTCH CONFIGURATION WILL VARY PER VENDOR'S DISCRETION.
	XXXXX-0YY 30u"/0.76u MIN GXT OVER 50u"/1.27u MIN Ni	
	NOTES	(10) BERGSTRIP™ PART NUMBERS FOLLOWED BY BY A "B" ARE BULK PRICED.
	1) PART NUMBER OPTIONS:	11) TAIL LENGTH (DIM. G) TO BE ±.008/.0.20.
\bigcirc	PIN PLATING CODES (SEE ABOVE) HIGH TEMPERATURE MATERIAL:	12. POSITIONS PER ROW 37 TO 50 CAN BE PRODUCED, BUT FLATNESS AND CURVATURE MAY NOT BE HELD AS CLOSE AS 36 POSITIONS.
	FOR HIGH-TEMPERATURE APPLICATIONS, SPECIFY AN "H" AT THE END OF THE PART NUMBER, AND PCT WILL BE SUPPLIED.	13) THESE PRODUCTS MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATION AS DESCRIBED IN GS-22-008.
	NUMBER OF POSITIONS :	(4) PLATING OPTIONS: MAY BE EITHER GOLD OR GXT PLATED AT MANUFACTURER'S OPTION.
В	EVEN NUMBER OF POSITIONS FROM 2 (2X1) THROUGH 72 (2X36). -X00H INDICATES BERGSTRIP PRODUCT. SEE PAGE 3 FOR SPECIAL GEOMETRY OF THIS CONTINUOUS STRIP PRODUCT. AUTOMATED REELS WILL CONTAIN 45,000 PINS. SEE SPECIFIC PART NUMBERS FOR AVAILABILITY.	(5) "THIS PRODUCT HAS 100% TIN PLATING IN THE INTERFACE AND HAS NOT BEEN TESTED FOR WHISKER GROWTH IN ALL INTERCONNECT ENVIRONMENTS."
tc 🔐	PACKAGING:	(16) THE OAL DON'T EXCEED 34.5mm
Jonnect.co	PACKAGED IN POLY BAGS. EIGHT DIGIT PART NUMBERS FOLLOWED BY A "T" ARE PACKAGED	(17) INCREMENTS BY 0.1mm IN LENGTHS ONLY
	IN TUBES. SEE SPECIFIC PART NUMBERS FOR AVAILABILITY. EIGHT DIGIT PART NUMBERS FOLLOWED BY A "G" ARE PACKAGED IN GPAX FOR IBM ONLY. SEE SPECIFIC PART NUMBERS FOR AVAILABILITY.	18. FOR SPECIAL PACKAGING REQUEST PLEASE CONTACT PRODUCT MANAGER FOR AVAILABILITY
	PART NUMBERS FOLLOWED BY A "C" ARE PACKAGED IN TUBES WITH A PICKUP CAP APPLIED.	
<u>c</u>	LEAD FREE: ADD "HLF" SUFFIX AT THE END OF PART NUMBER FOR LEAD FREE OPTION, NOT AVAILABLE FOR -5YY,-5YYH, -6YY & -6YYH	<u>c</u>
Copyright FCI	(2) BODY MATERIAL: BODY MATERIAL: MANUFACTURER'S OPTION OF NYLON, PCT GLASS FIBER REINFORCED OR MINERAL FILLED LCP FLAME RETARDENT PER UL-94V-0. COLOR: BLACK BERGSTRIP™ PRODUCED WITH HIGH TEMPERATURE LCP THERMOPLASTIC, FLAME RETARDENT PER UL-94V-0. COLOR: BLACK PART NUMBERS WITH "H" SUFFIX WILL WITHSTAND EXPOSURE TO 260' C PEAK TEMPERATURE FOR 20 SECONDS IN	mat/1. code SEE NOTES 2 & 3 S0 1902 Ultr ecn no dr date televarose untess otherwise specified BB angles linear 2. 1 S0 4007 Uncertain the specified specified substance untess otherwise specified specified to the specified s
O D	WAVE SOLDER, INFRA-RED OR VAPOR PHASE SOLDER PROCESS. PART NUMBERS WITHOUT "H" SUFFIX WILL WITHSTAND EXPOSURE TO 260' C PEAK TEMPERATURE FOR WAVE SOLDER PROCESS.	dr T.BREWBAKER 12/21/94 12/21/94 12/21/94 12/21/94 12/21/94 12/21/94 12/21/94 12/21/94 12/21/94 12/21/94 12/21/94 12/21/94 12/21/94 12/21/94 12/21/94 12/21/94 12/21/94 12/21/94 12/21/94 12/21/94
_	forms AB 1 2	3 4 5 6











