



ALL NEW PRODUCTS!



# Heyco® Rubber Grommets

Mounting Diameter: 0.562" to 0.875"

PANEL DIMENSIONS				PART NO.	DESCRIPTION	PART DIMENSIONS					
Maximum Thickness		Mounting Hole Diameter				Black	A Inside Diameter		B Head Diameter		C Overall Height
in.	mm.	in.	mm.		in.		mm.	in.	mm.	in.	mm.
.250	6,4	.562	14,3	<b>G1117</b>	RG 562-10-8	.313	8,0	.813	20,7	.500	12,7
.188	4,8	.562	14,3	<b>G1120</b>	RG 562-12-6	.375	9,5	.813	20,7	.375	9,5
.375	9,5	.562	14,3	<b>G1121</b>	RG 562-12-12	.375	9,5	.750	19,1	.750	19,1
.063	1,6	.562	14,3	<b>G1123</b>	RG 562-14-2	.438	11,1	.750	19,1	.250	6,4
.125	3,2	.625	15,9	<b>G1127</b>	RG 625-6-4	.188	4,8	.875	22,2	.250	6,4
.063	1,6	.625	15,9	<b>G1130</b>	RG 625-12-2	.375	9,5	.875	22,2	.313	8,0
.125	3,2	.625	15,9	<b>G1132</b>	RG 625-12-4	.375	9,5	.875	22,2	.375	9,5
.188	4,8	.625	15,9	<b>G1133</b>	RG 625-12-6	.375	9,5	.875	22,2	.438	11,1
.250	6,4	.625	15,9	<b>G1134</b>	RG 625-12-8	.375	9,5	.875	22,2	.500	12,7
.187	4,7	.625	15,9	<b>G1135</b>	RG 625-13-6	.400	10,2	1.100	27,9	.435	11,1
.375	9,5	.625	15,9	<b>G1136</b>	RG 625-13-12	.406	10,3	.813	20,7	.625	15,9
.063	1,6	.625	15,9	<b>G1137</b>	RG 625-16-2	.500	12,7	.813	20,7	.281	7,1
.110	2,8	.630	16,0	<b>G1140</b>	RG 630-16-4	.500	12,7	.810	20,6	.300	7,6
.063	1,6	.687	17,5	<b>G1150</b>	RG 687-14-2	.438	11,8	.938	23,8	.313	8,0
.063	1,6	.687	17,5	<b>G1151</b>	RG 687-14-2A	.438	11,1	.938	23,8	.348	8,8
.125	3,2	.687	17,5	<b>G1152</b>	RG 687-14-4	.438	11,1	.938	23,8	.375	9,5
.188	4,8	.687	17,5	<b>G1153</b>	RG 687-14-6	.438	11,1	.938	23,8	.438	11,1
.250	6,4	.687	17,5	<b>G1154</b>	RG 687-14-8	.438	11,1	.938	23,8	.500	12,7
.063	1,6	.687	17,5	<b>G1155</b>	RG 687-16-2	.500	12,7	.875	22,2	.250	6,4
.188	4,8	.750	19,1	<b>G1172</b>	RG 750-10-6	.313	8,0	1.000	25,4	.438	11,1
.063	1,6	.750	19,1	<b>G1174</b>	RG 750-12-2	.375	9,5	1.000	25,4	.375	9,5
.063	1,6	.750	19,1	<b>G1176</b>	RG 750-16-2	.500	12,7	.875	22,2	.250	6,4
.063	1,6	.750	19,1	<b>G1177</b>	RG 750-16-2A	.500	12,7	1.000	25,4	.250	6,4
.094	2,4	.750	19,1	<b>G1178</b>	RG 750-16-3	.500	12,7	.875	22,2	.344	8,7
.094	2,4	.750	19,1	<b>G1179</b>	RG 750-16-3A	.500	12,7	.969	24,6	.281	7,1
.156	4,0	.750	19,1	<b>G1181</b>	RG 750-16-5	.500	12,7	.938	23,8	.406	10,3
.375	9,5	.750	19,1	<b>G1182</b>	RG 750-16-12	.500	12,7	1.000	25,4	.625	15,9
.125	3,2	.812	20,6	<b>G1188</b>	RG 812-12-4	.375	9,5	1.063	27,0	.375	9,5
.313	8,0	.812	20,6	<b>G1191</b>	RG 812-14-10	.438	11,1	1.063	27,0	.625	15,9
.063	1,6	.812	20,6	<b>G1192</b>	RG 812-16-2	.500	12,7	1.063	27,0	.313	8,0
.125	3,2	.812	20,6	<b>G1193</b>	RG 812-16-4	.500	12,7	1.063	27,0	.375	9,5
.188	4,8	.812	20,6	<b>G1194</b>	RG 812-16-6	.500	12,7	1.063	27,0	.438	11,1
.250	6,4	.812	20,6	<b>G1195</b>	RG 812-16-8	.500	12,7	1.063	27,0	.500	12,7
.063	1,6	.812	20,6	<b>G1197</b>	RG 812-18-2	.563	14,3	1.063	27,0	.313	8,0
.125	3,2	.812	20,6	<b>G1198</b>	RG 812-18-4	.563	14,3	1.062	26,9	.375	9,5
.188	4,8	.812	20,6	<b>G1199</b>	RG 812-18-6	.563	14,3	1.063	27,0	.438	11,1
.250	6,4	.812	20,6	<b>G1200</b>	RG 812-18-8	.563	14,3	1.063	27,0	.500	12,7
.063	1,6	.875	22,2	<b>G1208</b>	RG 875-10-2	.313	8,0	1.375	34,9	.250	6,4
.188	4,8	.875	22,2	<b>G1213</b>	RG 875-18-6	.563	14,3	1.063	27,0	.438	11,1
.375	9,5	.875	22,2	<b>G1214</b>	RG 875-18-12	.563	14,3	1.063	27,0	.625	15,9

Standard color black.

- Used to protect or cover through holes. Help eliminate sharp edges so your wires are protected and add aesthetic value to your application.
- 160 sizes available that will accommodate mounting holes ranging from .250" (6,4 mm) to holes as large as 2.50" (63,5 mm) diameter and panel thicknesses from .063" (1,6 mm) to .375" (9,5 mm).
- Rubber grommets are constructed of SBR with an operating temperature range of -40°F (-40°C) to 221°F (105°C).
- SBR grommets have good water resistant characteristics and are suitable for most moderate chemicals and wet or dry organic acids.

