


JKL LAMP PART NUMBER	COLOR	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS (CANDELA/m ²)	*RATED LIFE (HRS)
BF20218-24B	LCD HIGH OUTPUT WHITE 8400°k RGB	1700 @ 0°C	740	5	38,000 ± 10%	20,000

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

			METRIC  THIRD ANGLE PROJECTION		DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0 ANGLE +/- 0		JKL COMPONENTS CORPORATION					
					TITLE MINIATURE COLD CATHODE FLUORESCENT LAMP							
A CHANGE MECH. ART RELEASED			1/21/03 11/4/02	DRAWN BY L. WENGSTROM	APP'VD BY DATE L.W. 1/21/03	SIZE A	FSCM NO. 55335	DRAWING NO. BF20218-24B				
REV. NO. DESCRIPTION/ECO NUMBER			APP'VD DATE	- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED		SCALE NONE	RELEASED DATE 11/4/02	REVISION DATE 1/21/03	REV. NO. A	SHEET 1 OF 1		