



NOTES:

- MATERIALS:
HOUSING: POLYESTER (PBT), GLASS FILLED, UL94 V-0,
COLOR: BLACK.
- PRODUCT SPECIFICATION: TBD. (A)
- PACKAGING SPECIFICATION: PK-19436-001.
- USE WITH MALE CRIMP TERMINAL SERIES 19431. (A)
- MATES WITH 19432 SERIES RECEPTACLE ASSEMBLIES. (A)
- RECOMMENDED MOUNTING HARDWARE: (2)#10 X .62/18.9 LONG PLASTIC
THREAD CUTTING SCREWS. RECOMMENDED TORQUE 15-17 IN.-LBS.
SUGGESTED SOURCE: ITW SHAKEPROOF INDUSTRIAL BOSSCREW OR EQUIVALENT.
- ASSEMBLY IS ROHS COMPLIANT.

19436-0214	8	YES
19436-0213	12-10	YES
19436-0212	8	NO
19436-0211	12-10	NO
MATERIAL NUMBER	WIRE AWG	PANEL GASKET

RVSD NOTES 3 & 5. EC NO: ETC2008-0085 DRAWN: JPWLICK 2007/09/21 CHKCD: JPWLICK 2007/09/21 APPR: JPWLICK 2007/09/21	QUALITY SYMBOLS ▽=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE IN/MM		SCALE 2:1	DESIGN UNITS INCH	THIRD ANGLE PROJECTION	
		4 PLACES ± --- ± ---	mm INCH	DRAWN BY JPWLICK	DATE 01/08/07	TITLE 2 WAY SEALED PLUG PANEL MOUNT ASSEMBLY, 12-10 & 8 AWG			
		3 PLACES ± --- ± .015		CHECKED BY JPWLICK	DATE 01/09/07	MOLEX INCORPORATED			
		2 PLACES ± 0.38 ± ---		APPROVED BY JPWLICK	DATE 01/10/07	MATERIAL NO. SD-19436-001	DOCUMENT NO.	SHEET NO. 1 OF 1	
1 PLACE ± --- ± ---		ANGULAR ± 1 °		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SEE CHART		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION	