Part Numbering

Chip Ferrite Beads for Automotive

Product ID

Product ID	
BL	Chip Ferrite Beads

2Туре

Code	Туре
М	Monolithic Type

3Dimensions (LXW)

Code	Dimensions (LXW)	EIA
15	1.0×0.5mm	0402
18	1.6×0.8mm	0603
21	2.0×1.25mm	0805
31	3.2×1.6mm	1206
41	4.5×1.6mm	1806

4 Characteristics/Applications

Code *1	Characteristics/Applications	Series	
AG	for General Use	BLM15/18/21/31	
AJ	Tor General Use	DLIVI 13/16/21/31	
ВА		BLM18	
ВВ	for High-speed Signal Lines	BLM15/18/21	
BD		BLW113/18/21	
PG	for Power Supplies BLM18/21/		
HG	for GHz Band General Use		
EG	for GHz Band General Use (Low DC Resistance Type)	BLM18	
HD	for GHz Band High-speed Signal Lines		

^{*1} Frequency characteristics vary with each code.

5Impedance

Expressed by three figures. The unit is in ohm (Ω). The first and second figures are significant digits, and the third figure expresses the number of zeros which follow the two figures.

6Electrode

Expressed by a letter.

Ex.)	Code	Electrode
	S/T	Sn Plating
	W	Ag/Pd

Category

Code	Category
Н	for Automotive

8 Number of Circuits

Code	Number of Circuits
1	1 Circuit

Packaging

Code	Packaging	Series	
K	Embossed Taping (ø330mm Reel)	BLM21 *1/31/41	
L	Embossed Taping (ø180mm Reel)	DLW21 1/31/41	
В	Bulk	All Series	
J	Paper Taping (ø330mm Reel)	BLM15/18/21 *2	
D	Paper Taping (ø180mm Reel)	— BLW13/10/21 2	

^{*1} BLM21BD222SH1/BLM21BD272SH1 only.

^{*2} Except BLM21BD222SH1/BLM21BD272SH1