

## FEATURES

- Economical
- Applications include commercial, industrial and communications equipment
- Stability under high temperature conditions
- All-welded construction
- RoHS compliant; add "E" suffix to part number to specify.

## SPECIFICATIONS

### Material

**Coating:** Conformal silicone-ceramic.

**Core:** Ceramic.

**Terminals:** Solder-coated copper clad axial. RoHS solder composition is 96% Sn, 3.5% Ag, 0.5% Cu

### Derating

Linearly from  
100% @ +25°C to  
0% @ +275°C.

### Electrical

**Tolerance:** ±5% (J type), ±1% (F type) (other tolerances available).

**Power rating:** Based on 25°C free air rating (other wattages available).

**Overload:** Under 5 watts: 5 times rated wattage for 5 seconds. 5 watts and over: 10 times rated wattage for 5 seconds.

**Temperature coefficient:**  
Under 1Ω: ±90 ppm/°C  
1Ω to 9.99Ω: ±50 ppm/°C  
10Ω and over: ±20 ppm/°C

### ORDERING INFO

40 Series  
Ohmicone®  
Silicone Ceramic  
Conformal Axial  
Term. Wirewound

Non-Inductive  
Winding  
Optional (blank  
= std. winding)

RoHS  
Compliant


41NJR10E

Wattage	Tolerance	Resistance Value
1 = 1W	F = 1%	R10 = 0.10Ω
2	J = 5%	1R0 = 1.0Ω
3		10R = 10.0Ω
5		250 = 250Ω
7		1K0 = 1,000Ω
0 = 10W		4K5 = 4,500Ω
		50K = 50,000Ω



## 40 Series

### Ohmicone® Silicone-Ceramic Conformal Axial Term. Wirewound, 1% and 5% Tol. Std.



Series	Wattage	Ohms	Dimensions (in. / mm)		Lead Voltage	ga.
			Length	Diam.		
41	1.0	0.10-6K	0.437 / 11.1	0.125 / 3.2	150	24
42	2.0	0.10-8K	0.406 / 10.3	0.219 / 5.6	100	20
43	3.0	0.10-20K	0.593 / 15.1	0.218 / 5.5	200	20
45	5.0	0.10-70K	0.937 / 23.8	0.343 / 8.7	460	18
47	7.0	0.10-80K	1.280 / 32.5	0.343 / 8.7	670	18
40	10.0	0.10-150K	1.642 / 41.7	0.406 / 10.3	1000	18

Non-Inductive versions available. Insert "N" before tolerance code. Example: 42NJR27R

Ohmite 40 Series resistors are the most economical conformal silicone-ceramic coated resistors offered. These all-welded units are characterized by their low temperature coefficients and resistance to thermal shock, making them ideal for a wide range of electrical and electronic applications.

Units with 1% and 5% tolerances are identical in construction and electrical specifications. Durable but economical 40 Series resistors exceed industry requirements for quality.

### STANDARD PART NUMBERS FOR 40 SERIES

Ohmic value	Wattage and Tolerance									
	1% Tolerance					5% Tolerance				
Part No. Prefix ▶ Suffix ▼	1	3	5	10	1	2	3	5	10	
0.1	✓	✓	✓	✓	✓	✓	✓	✓	✓	68
0.15	✓	✓	✓	✓	✓	✓	✓	✓	✓	75
0.2	✓	✓	✓	✓	✓	✓	✓	✓	✓	82
0.25	✓	✓	✓	✓	✓	✓	✓	✓	✓	100
0.3	✓	✓	✓	✓	✓	✓	✓	✓	✓	120
0.33	✓	✓	✓	✓	✓	✓	✓	✓	✓	125
0.4	✓	✓	✓	✓	✓	✓	✓	✓	✓	150
0.5	✓	✓	✓	✓	✓	✓	✓	✓	✓	180
0.75	✓	✓	✓	✓	✓	✓	✓	✓	✓	200
1	✓	✓	✓	✓	✓	✓	✓	✓	✓	220
1.5	✓	✓	✓	✓	✓	✓	✓	✓	✓	225
2	✓	✓	✓	✓	✓	✓	✓	✓	✓	250
2.2	✓	✓	✓	✓	✓	✓	✓	✓	✓	270
3	✓	✓	✓	✓	✓	✓	✓	✓	✓	300
4	✓	✓	✓	✓	✓	✓	✓	✓	✓	330
5	✓	✓	✓	✓	✓	✓	✓	✓	✓	350
7.5	✓	✓	✓	✓	✓	✓	✓	✓	✓	390
10	✓	✓	✓	✓	✓	✓	✓	✓	✓	400
12	✓	✓	✓	✓	✓	✓	✓	✓	✓	450
15	✓	✓	✓	✓	✓	✓	✓	✓	✓	470
18	✓	✓	✓	✓	✓	✓	✓	✓	✓	500
20	✓	✓	✓	✓	✓	✓	✓	✓	✓	560
22	✓	✓	✓	✓	✓	✓	✓	✓	✓	600
25	✓	✓	✓	✓	✓	✓	✓	✓	✓	680
27	✓	✓	✓	✓	✓	✓	✓	✓	✓	750
30	✓	✓	✓	✓	✓	✓	✓	✓	✓	800
33	✓	✓	✓	✓	✓	✓	✓	✓	✓	820
35	✓	✓	✓	✓	✓	✓	✓	✓	✓	900
39	✓	✓	✓	✓	✓	✓	✓	✓	✓	1,000
40	✓	✓	✓	✓	✓	✓	✓	✓	✓	1,100
47	✓	✓	✓	✓	✓	✓	✓	✓	✓	1,200
50	✓	✓	✓	✓	✓	✓	✓	✓	✓	1,500
56	✓	✓	✓	✓	✓	✓	✓	✓	✓	1,800
62	✓	✓	✓	✓	✓	✓	✓	✓	✓	2,000

Shaded values involve very fine resistance wire and should not be used in critical applications without burn-in and/or thermal cycling.

✓ = Standard values

✗ = Non-standard values subject to minimum handling charge per item

Check product availability at [www.ohmite.com](http://www.ohmite.com)