

ST280CH..C SERIES

PHASE CONTROL THYRISTORS

Hockey Puk Version

Features

- Center amplifying gate
- Metal case with ceramic insulator
- International standard case TO-200AB (A-PUK)
- Extended temperature range


500A

Typical Applications

- DC motor controls
- Controlled DC power supplies
- AC controllers

Major Ratings and Characteristics

Parameters	ST280CH..C	Units
$I_{T(AV)}$	500	A
@ T_{hs}	80	°C
$I_{T(RMS)}$	1130	A
@ T_{hs}	25	°C
I_{TSM}	7200	A
@ 50Hz	7200	A
@ 60Hz	7500	A
I^2t	260	KA ² s
@ 50Hz	260	KA ² s
V_{DRM}/V_{RRM}	400 to 600	V
t_q typical	100	μs
T_J	- 40 to 150	°C



case style TO-200AB (A-PUK)

ST280CH..C Series

Bulletin I25160 rev. C 02/00

International
IR Rectifier

ELECTRICAL SPECIFICATIONS

Voltage Ratings

Type number	Voltage Code	V_{DRM}/V_{RRM} , max. repetitive peak and off-state voltage V	V_{RSM} , maximum non-repetitive peak voltage V	I_{DRM}/I_{RRM} max. @ $T_J = T_{J\max}$ mA
ST280CH..C	04	400	500	75
	06	600	700	

On-state Conduction

Parameter	ST280CH..C	Units	Conditions
$I_{T(AV)}$	500 (185)	A	180° conduction, half sine wave
	80 (110)	°C	double side (single side) cooled
$I_{T(RMS)}$	1130	A	DC @ 25°C heatsink temperature double side cooled
I_{TSM}	7200		$t = 10ms$ No voltage reapplied
	7500		$t = 8.3ms$
	6000		$t = 10ms$ 100% V_{RRM}
	6300		$t = 8.3ms$ reapplied
I^2t	260	KA ² s	Sinusoidal half wave, Initial $T_J = T_{J\max}$
	235		$t = 10ms$ No voltage reapplied
	180		$t = 8.3ms$
	165		$t = 10ms$ 100% V_{RRM}
I^2/\sqrt{t}	2600	KA ² /s	$t = 0.1$ to 10ms, no voltage reapplied
$V_{T(TO)1}$	0.84	V	(16.7% $\times \pi \times I_{T(AV)} < I < \pi \times I_{T(AV)}$), $T_J = T_{J\max}$
$V_{T(TO)2}$	0.88		($I > \pi \times I_{T(AV)}$), $T_J = T_{J\max}$
r_{t1}	0.50	mΩ	(16.7% $\times \pi \times I_{T(AV)} < I < \pi \times I_{T(AV)}$), $T_J = T_{J\max}$
r_{t2}	0.47		($I > \pi \times I_{T(AV)}$), $T_J = T_{J\max}$
V_{TM}	1.35	V	$I_{pk} = 1000A$, $T_J = T_{J\max}$, $t_p = 10ms$ sine pulse
I_H	600	mA	$T_J = 25^\circ C$, anode supply 12V resistive load
I_L	1000 (300)		

Switching

Parameter	ST280CH..C	Units	Conditions	
di/dt	Max. non-repetitive rate of rise of turned-on current	A/μs	Gate drive 20V, 20Ω, $t_r \leq 1\mu s$ $T_J = T_{J\max}$, anode voltage $\leq 80\% V_{DRM}$	
t_d	Typical delay time	1.0	μs	Gate current 1A, $di_g/dt = 1A/\mu s$ $V_d = 0.67\% V_{DRM}$, $T_J = 25^\circ C$
t_q	Typical turn-off time	100		$I_{TM} = 300A$, $T_J = T_{J\max}$, $di/dt = 20A/\mu s$, $V_R = 50V$ $dv/dt = 20V/\mu s$, Gate 0V 100Ω, $t_p = 500\mu s$

Blocking

Parameter	ST280CH..C	Units	Conditions
dv/dt Maximum critical rate of rise of off-state voltage	500	V/ μ s	$T_J = T_J$ max, linear to 80% rated V_{DRM}
I_{DRM} Max. peak reverse and off-state leakage current	75	mA	$T_J = T_J$ max, rated V_{DRM}/V_{RRM} applied

Triggering

Parameter	ST280CH..C	Units	Conditions
P_{GM} Maximum peak gate power	10.0	W	$T_J = T_J$ max, $t_p \leq 5ms$
$P_{G(AV)}$ Maximum average gate power	2.0		$T_J = T_J$ max, $f = 50Hz$, $d\% = 50$
I_{GM} Max. peak positive gate current	3.0	A	$T_J = T_J$ max, $t_p \leq 5ms$
+ V_{GM} Maximum peak positive gate voltage	20	V	$T_J = T_J$ max, $t_p \leq 5ms$
- V_{GM} Maximum peak negative gate voltage	5.0		
I_{GT} DC gate current required to trigger	TYP. 180 90 30	MAX. - 150 -	mA $T_J = -40^{\circ}C$ $T_J = 25^{\circ}C$ $T_J = 150^{\circ}C$ Max. required gate trigger/ current/voltage are the lowest value which will trigger all units 12V anode-to-cathode applied
V_{GT} DC gate voltage required to trigger	2.9 1.8 1.0	- 3.0 -	V $T_J = -40^{\circ}C$ $T_J = 25^{\circ}C$ $T_J = 150^{\circ}C$
I_{GD} DC gate current not to trigger	10	mA	
V_{GD} DC gate voltage not to trigger	0.30	V	$T_J = T_J$ max Max. gate current/voltage not to trigger is the max. value which will not trigger any unit with rated V_{DRM} anode-to-cathode applied

Thermal and Mechanical Specification

Parameter	ST280CH..C	Units	Conditions
T_J Max. operating temperature range	-40 to 150	$^{\circ}$ C	
T_{stg} Max. storage temperature range	-40 to 150		
R_{thJ-hs} Max. thermal resistance, junction to heatsink	0.17 0.08	K/W	DC operation single side cooled DC operation double side cooled
R_{thC-hs} Max. thermal resistance, case to heatsink	0.033 0.017	K/W	DC operation single side cooled DC operation double side cooled
F Mounting force, $\pm 10\%$	4900 (500)	N (Kg)	
wt Approximate weight	50	g	
Case style	TO - 200AB (A-PUK)		See Outline Table

ST280CH..C Series

Bulletin I25160 rev. C 02/00


International
IR Rectifier

$\Delta R_{th,I-hs}$ Conduction

(The following table shows the increment of thermal resistance $R_{th,I-hs}$ when devices operate at different conduction angles than DC)

Conduction angle	Sinusoidal conduction		Rectangular conduction		Units	Conditions
	Single Side	Double Side	Single Side	Double Side		
180°	0.016	0.017	0.011	0.011	K/W	$T_J = T_{J_{\max}}$
120°	0.019	0.019	0.019	0.019		
90°	0.024	0.024	0.026	0.026		
60°	0.035	0.035	0.036	0.037		
30°	0.060	0.060	0.060	0.061		

Ordering Information Table



Outline Table





Fig. 1 - Current Ratings Characteristics




Fig. 2 - Current Ratings Characteristics

ST280C..H Series

Bulletin I25160 rev. C 02/00

International
IR Rectifier




Fig. 3 - Current Ratings Characteristics




Fig. 4 - Current Ratings Characteristics




Fig. 5 - On-state Power Loss Characteristics




Fig. 6 - On-state Power Loss Characteristics




Fig. 7 - Maximum Non-Repetitive Surge Current
Single and Double Side Cooled




Fig. 8 - Maximum Non-Repetitive Surge Current
Single and Double Side Cooled

Instantaneous On-state Current (A)

Instantaneous On-state Voltage (V)

Fig. 9 - On-state Voltage Drop Characteristics

Transient Thermal Impedance Z_{thJ-hs} (K/W)

Square Wave Pulse Duration (s)

Fig. 10 - Thermal Impedance Z_{thJ-hs} Characteristics

Instantaneous Gate Voltage (V)

Instantaneous Gate Current (A)

Fig. 11 - Gate Characteristics



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.