

## Inductors

Epoxy Conformal Coated  
Uniform Roll Coated



### FEATURES

- Flame-retardant coating
- Color band identification
- Excellent environmental characteristics
- Uniform coating is excellent for automatic insertion
- Comparable in quality to molded chokes at a lower price
- Epoxy coating is more durable than lacquer coated models, yet is priced comparably



**RoHS**  
COMPLIANT

### ELECTRICAL SPECIFICATIONS

**Inductance Tolerance:** ± 1 %, ± 3 %, ± 5 %, ± 10 %, ± 20 %  
Other tolerances available on request

**Insulation Resistance:** 1000 Megohm minimum per MIL-STD-202, Method 302, Test Condition B

**Dielectric Strength:** 1000 VAC per MIL-STD-202, Method 301

### MATERIAL SPECIFICATIONS

**Coating:** Epoxy-uniform roll coated

**Lead:** Tinned copper

### MECHANICAL SPECIFICATIONS

**Terminal Strength:** 5 pounds pull per MIL-STD-202, Method 211, Test Condition A

**Weight:** IR-2 = 0.30 grams maximum  
IR-4 = 0.65 gram maximum

### TEST EQUIPMENT\*

- H/P 4342A Q-Meter
- Measurements Corporation Megacycle Meter, Model 59
- Wheatstone bridge

\* Test procedures per MIL-PRF-15305

DIMENSIONS in inches [millimeters]				
MODEL	A (Max.)	B (Max.)	C (Max.)	D
IR-2	0.260 [6.60]	0.120 [3.05]	0.330 [8.38]	0.0200 ± 0.0015 [0.508 ± 0.038]
IR-4	0.385 [9.78]	0.180 [4.57]	0.440 [11.18]	0.025 ± 0.002 [0.635 ± 0.051]

ENVIRONMENTAL PERFORMANCE		
TEST	CONDITIONS	SPECIFICATIONS
Barometric Pressure	Test Condition C	MIL-STD-202, Method 105
Thermal Shock	Test Condition A-1	MIL-STD-202, Method 107
Flammability	-	MIL-STD-202, Method 111
Overload	-	MIL-PRF-15305
Low Temperature	-	MIL-PRF-15305
Resistance to Soldering Heat	Test Condition A	MIL-STD-202, Method 210
Resistance to Solvents	-	MIL-STD-202, Method 215

MAXIMUM TEMPERATURE RISE									
<b>IR-2</b>	<table border="0"> <tr> <td style="padding-right: 20px;">0.1 μH to 1.0 μH = + 35 °C at + 90 °C ambient</td> <td style="text-align: center;">- 55 °C to 125 °C</td> </tr> <tr> <td style="padding-right: 20px;">1.2 μH to 27 μH = + 15 °C at + 90 °C ambient</td> <td style="text-align: center;">- 55 °C to 105 °C</td> </tr> <tr> <td style="padding-right: 20px;">33 μH to 1000 μH = + 15 °C at + 90 °C ambient</td> <td style="text-align: center;">- 55 °C to 105 °C</td> </tr> </table>	0.1 μH to 1.0 μH = + 35 °C at + 90 °C ambient	- 55 °C to 125 °C	1.2 μH to 27 μH = + 15 °C at + 90 °C ambient	- 55 °C to 105 °C	33 μH to 1000 μH = + 15 °C at + 90 °C ambient	- 55 °C to 105 °C		
0.1 μH to 1.0 μH = + 35 °C at + 90 °C ambient	- 55 °C to 125 °C								
1.2 μH to 27 μH = + 15 °C at + 90 °C ambient	- 55 °C to 105 °C								
33 μH to 1000 μH = + 15 °C at + 90 °C ambient	- 55 °C to 105 °C								
<b>IR-4</b>	<table border="0"> <tr> <td style="padding-right: 20px;">0.15 μH to 4.7 μH = + 35 °C at + 90 °C ambient</td> <td style="text-align: center;">- 55 °C to 125 °C</td> </tr> <tr> <td style="padding-right: 20px;">5.6 μH to 33 μH = + 15 °C at + 90 °C ambient</td> <td style="text-align: center;">- 55 °C to 105 °C</td> </tr> <tr> <td style="padding-right: 20px;">36 μH to 240 μH = + 15 °C at + 90 °C ambient</td> <td style="text-align: center;">- 55 °C to 105 °C</td> </tr> <tr> <td style="padding-right: 20px;">270 μH to 1800 μH = + 35 °C at + 90 °C ambient</td> <td style="text-align: center;">- 55 °C to 125 °C</td> </tr> </table>	0.15 μH to 4.7 μH = + 35 °C at + 90 °C ambient	- 55 °C to 125 °C	5.6 μH to 33 μH = + 15 °C at + 90 °C ambient	- 55 °C to 105 °C	36 μH to 240 μH = + 15 °C at + 90 °C ambient	- 55 °C to 105 °C	270 μH to 1800 μH = + 35 °C at + 90 °C ambient	- 55 °C to 125 °C
0.15 μH to 4.7 μH = + 35 °C at + 90 °C ambient	- 55 °C to 125 °C								
5.6 μH to 33 μH = + 15 °C at + 90 °C ambient	- 55 °C to 105 °C								
36 μH to 240 μH = + 15 °C at + 90 °C ambient	- 55 °C to 105 °C								
270 μH to 1800 μH = + 35 °C at + 90 °C ambient	- 55 °C to 125 °C								



STANDARD ELECTRICAL SPECIFICATIONS								
MODEL	IND. (µH)	TOL.	Q MIN.	TEST FREQ. L & Q (MHz)	SELF-RESONANT* FREQ MIN. (MHz)	DCR MAX. (Ohms)	RATED DC** CURRENT (mA)	
IR-2	0.10	± 10 %	40	25.0	680.0	0.08	1350	PHENOLIC CORE
IR-2	0.12	± 10 %	40	25.0	640.0	0.09	1270	
IR-2	0.15	± 10 %	38	25.0	600.0	0.10	1200	
IR-2	0.18	± 10 %	35	25.0	550.0	0.12	1105	
IR-2	0.22	± 10 %	33	25.0	510.0	0.14	1025	
IR-2	0.27	± 10 %	33	25.0	430.0	0.16	960	
IR-2	0.33	± 10 %	30	25.0	410.0	0.22	815	
IR-2	0.39	± 10 %	30	25.0	365.0	0.30	700	
IR-2	0.47	± 10 %	30	25.0	330.0	0.35	650	
IR-2	0.56	± 10 %	30	25.0	300.0	0.50	545	
IR-2	0.68	± 10 %	28	25.0	275.0	0.60	495	
IR-2	0.82	± 10 %	28	25.0	250.0	0.85	415	
IR-2	1.0	± 10 %	25	25.0	230.0	1.00	385	
IR-2	1.2	± 10 %	25	7.9	150.0	0.18	590	IRON CORE
IR-2	1.5	± 10 %	28	7.9	140.0	0.22	535	
IR-2	1.8	± 10 %	30	7.9	125.0	0.30	455	
IR-2	2.2	± 10 %	30	7.9	115.0	0.40	395	
IR-2	2.7	± 10 %	37	7.9	100.0	0.55	355	
IR-2	3.3	± 10 %	45	7.9	90.0	0.85	270	
IR-2	3.9	± 10 %	45	7.9	80.0	1.0	250	
IR-2	4.7	± 10 %	45	7.9	75.0	1.2	230	
IR-2	5.6	± 10 %	50	7.9	65.0	1.8	185	
IR-2	6.8	± 10 %	50	7.9	60.0	2.0	175	
IR-2	8.2	± 10 %	55	7.9	55.0	2.7	155	
IR-2	10.0	± 10 %	55	7.9	50.0	3.7	130	
IR-2	12.0	± 10 %	45	2.5	40.0	2.7	155	
IR-2	15.0	± 10 %	40	2.5	35.0	2.8	150	
IR-2	18.0	± 10 %	50	2.5	30.0	3.1	145	
IR-2	22.0	± 10 %	50	2.5	25.0	3.3	140	
IR-2	27.0	± 10 %	50	2.5	20.0	3.5	135	
IR-2	33.0	± 10 %	45	2.5	24.0	3.4	130	FERRITE CORE
IR-2	39.0	± 10 %	45	2.5	22.0	3.6	125	
IR-2	47.0	± 10 %	45	2.5	20.0	4.5	110	
IR-2	56.0	± 10 %	45	2.5	18.0	5.7	100	
IR-2	68.0	± 10 %	50	2.5	15.0	6.7	92	
IR-2	82.0	± 10 %	50	2.5	14.0	7.3	88	
IR-2	100.0	± 10 %	50	2.5	13.0	8.0	84	
IR-2	120.0	± 10 %	30	0.79	12.0	13.0	66	
IR-2	150.0	± 10 %	30	0.79	11.0	15.0	61	
IR-2	180.0	± 10 %	30	0.79	10.0	17.0	57	
IR-2	220.0	± 10 %	30	0.79	9.0	21.0	52	
IR-2	270.0	± 10 %	30	0.79	8.0	25.0	47	
IR-2	330.0	± 10 %	30	0.79	7.0	28.0	45	
IR-2	390.0	± 10 %	30	0.79	6.5	35.0	40	
IR-2	470.0	± 10 %	30	0.79	6.0	42.0	36	
IR-2	560.0	± 10 %	30	0.79	5.0	46.0	35	
IR-2	680.0	± 10 %	30	0.79	4.0	60.0	30	
IR-2	820.0	± 10 %	30	0.79	3.8	65.0	29	
IR-2	1000.0	± 10 %	30	0.79	3.4	72.0	28	
IR-4	0.15	± 20 %	50	25.0	525.0	0.03	2450	PHENOLIC CORE
IR-4	0.22	± 20 %	50	25.0	450.0	0.055	1810	
IR-4	0.33	± 20 %	45	25.0	360.0	0.09	1400	
IR-4	0.47	± 20 %	45	25.0	310.0	0.12	1225	
IR-4	0.56	± 10 %	50	25.0	280.0	0.135	1150	
IR-4	0.68	± 10 %	50	25.0	250.0	0.15	1100	
IR-4	0.82	± 10 %	50	25.0	220.0	0.22	900	
IR-4	1.0	± 10 %	50	25.0	200.0	0.29	785	
IR-4	1.2	± 10 %	33	7.9	180.0	0.42	650	
IR-4	1.5	± 10 %	33	7.9	160.0	0.50	600	
IR-4	1.8	± 10 %	33	7.9	150.0	0.65	525	
IR-4	2.2	± 10 %	33	7.9	135.0	0.95	435	
IR-4	2.7	± 10 %	33	7.9	120.0	1.20	385	
IR-4	3.3	± 10 %	33	7.9	110.0	2.00	300	
IR-4	3.9	± 10 %	33	7.9	100.0	2.30	280	
IR-4	4.7	± 10 %	33	7.9	90.0	2.60	260	

\* Measured with full length lead.

\*\* Rated DC Current based on maximum temperature rise as shown in table.



STANDARD ELECTRICAL SPECIFICATIONS							
MODEL	IND. (μH)	TOL.	Q MIN.	TEST FREQ. L & Q (MHz)	SELF-RESONANT* FREQ MIN. (MHz)	DCR MAX. (Ohms)	RATED DC** CURRENT (mA)
IR-4	5.6	± 10 %	45	7.9	60.0	32.0	495
IR-4	6.8	± 10 %	50	7.9	55.0	0.50	395
IR-4	8.2	± 10 %	50	7.9	50.0	0.60	360
IR-4	10.0	± 10 %	55	7.9	45.0	0.90	290
IR-4	12.0	± 10 %	65	2.5	42.0	1.10	265
IR-4	15.0	± 10 %	65	2.5	40.0	1.40	240
IR-4	18.0	± 10 %	75	2.5	34.0	2.25	185
IR-4	22.0	± 10 %	75	2.5	30.0	2.50	175
IR-4	27.0	± 10 %	60	2.5	25.0	2.60	170
IR-4	33.0	± 10 %	65	2.5	19.0	3.0	165
IR-4	36.0	± 5 %	60	2.5	15.5	2.50	180
IR-4	39.0	± 5 %	60	2.5	14.5	2.60	176
IR-4	43.0	± 5 %	60	2.5	13.7	2.70	172
IR-4	47.0	± 5 %	55	2.5	13.0	2.75	170
IR-4	51.0	± 5 %	55	2.5	12.7	2.85	167
IR-4	56.0	± 5 %	55	2.5	12.0	3.0	164
IR-4	62.0	± 5 %	55	2.5	11.5	3.15	160
IR-4	68.0	± 5 %	55	2.5	11.0	3.30	156
IR-4	75.0	± 5 %	55	2.5	10.5	3.70	147
IR-4	82.0	± 5 %	50	2.5	10.3	3.90	143
IR-4	91.0	± 5 %	50	2.5	10.0	4.30	136
IR-4	100.0	± 5 %	50	2.5	9.5	4.50	133
IR-4	110.0	± 5 %	60	0.79	8.9	4.90	128
IR-4	120.0	± 5 %	65	0.79	8.7	5.20	124
IR-4	130.0	± 5 %	65	0.79	8.5	5.45	121
IR-4	150.0	± 5 %	65	0.79	8.0	6.05	114
IR-4	160.0	± 5 %	65	0.79	7.5	6.40	111
IR-4	180.0	± 5 %	65	0.79	7.0	6.75	108
IR-4	200.0	± 5 %	65	0.79	6.5	7.10	106
IR-4	220.0	± 5 %	65	0.79	6.2	7.45	103
IR-4	240.0	± 5 %	65	0.79	5.9	7.80	101
IR-4	270.0	± 5 %	65	0.79	5.7	11.0	129
IR-4	300.0	± 5 %	65	0.79	5.4	11.5	125
IR-4	330.0	± 5 %	65	0.79	5.1	12.0	123
IR-4	360.0	± 5 %	65	0.79	4.8	15.5	108
IR-4	390.0	± 5 %	65	0.79	4.5	16.3	105
IR-4	430.0	± 5 %	65	0.79	4.2	17.1	102
IR-4	470.0	± 5 %	65	0.79	3.9	17.9	100
IR-4	510.0	± 5 %	65	0.79	3.7	18.8	98
IR-4	560.0	± 5 %	65	0.79	3.5	24.7	85
IR-4	620.0	± 5 %	65	0.79	3.3	25.9	83
IR-4	680.0	± 5 %	55	0.79	3.1	27.2	81
IR-4	750.0	± 5 %	55	0.79	2.9	28.6	79
IR-4	820.0	± 5 %	55	0.79	2.7	30.0	77
IR-4	910.0	± 5 %	55	0.79	2.5	31.5	76
IR-4	1000.0	± 5 %	55	0.79	2.3	33.1	74
IR-4	1100.0	± 5 %	30	0.25	2.1	43.5	64
IR-4	1200.0	± 5 %	30	0.25	2.0	45.7	63
IR-4	1300.0	± 5 %	30	0.25	1.9	49.0	61
IR-4	1500.0	± 5 %	30	0.25	1.8	52.5	59
IR-4	1600.0	± 5 %	30	0.25	1.7	54.0	58
IR-4	1800.0	± 5 %	30	0.25	1.6	56.7	56

IRON CORE

\* Measured with full length lead.

\*\* Rated DC Current based on maximum temperature rise as shown in table.

DESCRIPTION				
IR-2	10 μH	± 10 %	ER	e2
MODEL	INDUCTANCE VALUE	INDUCTANCE TOLERANCE	PACKAGE CODE	JEDEC LEAD (Pb)-FREE STANDARD

GLOBAL PART NUMBER INFORMATION			
I R 0 2	E R	1 0 0	K
MODEL	PACKING CODE	INDUCTANCE VALUE	TOL.



## Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.